

IN THE CLAIMS

1. (original) A photonic device comprising at least one integral waveguide formed from a REDGIVN (rare earth doped group iv nanocrystal) material.
2. (original) A photonic device according to claim 1 wherein the wave guide has a planar structure.
3. (currently amended) A photonic device according to claim 2, further comprising a substrate or a ~~and/or~~ bottom cladding, a layer containing the REDGIVN material, and a lateral containment element adapted to laterally confine light to a region within the layer containing the REDGIVN material where the at least one wave guide is to be defined.
4. (withdrawn) A photonic device according to claim 1 wherein the at least one wave guide is arranged to form a Mach Zehnder interferometer.
5. (withdrawn) A photonic device according to claim 1 wherein the at least one wave guide is arranged to form an optical splitter.
6. (original) A photonic device according to claim 1 further comprising: a pump source adapted to activate the nanocrystals in the wave guide which in turn activate the rare earth element in the REDGIVN.

7. (original) A photonic device according to claim 6 adapted to perform an amplification function upon an input optical signal to produce an amplified output optical signal.

8. (currently amended) A photonic device according to claim 7, further comprising a substrate or a ~~and/or~~ bottom cladding, a layer containing the REDGIVN material, and a lateral containment element adapted to laterally confine light to a region within the layer containing the REDGIVN material where the at least one wave guide is to be defined.

9. (original) A photonic device according to claim 7 wherein the pump source comprises an optical pump source.

10. (original) A photonic device according to claim 9 wherein the optical pump source comprises a broadband optical pump source.

11. (original) A photonic device according to claim 10 wherein the broadband optical pump source is arranged to transversely pump light into the at least one wave guide.

12. (currently amended) A photonic device according to claim 11, further comprising a substrate or a ~~and/or~~ bottom cladding, a layer containing the REDGIVN material, and a lateral containment element adapted to laterally confine light to a region within the layer containing the REDGIVN material where the at least one wave guide is to be defined,

wherein the lateral containment element comprises an etched ribbed channel of spin on glass.

13. (original) A photonic device according to claim 10 wherein the broadband source comprises at least one broadband LED (light emitting diode).

14. (original) A photonic device according to claim 13 wherein the at least one broadband LED comprises a plurality of broadband LEDs arranged to collectively transversely pump the at least one wave guide.

15. (original) A photonic device according to claim 13 further comprising coupling optics between each LED and the wave guide to focus light from the LED into the wave guide.

16. (original) A photonic device according to 15 further comprising a reflection chamber surrounding the device to contain light within the device.

17. (original) A photonic device according to claim 1 comprising an optical signal receiving surface through which light is received into the wave guide.

18. (original) A photonic device according to claim 14 wherein said at least one wave guide comprises a plurality of wave guides, and wherein each LED pumps the plurality of wave guides.

In re Patent Application of:

STEVEN HILL

Serial No. 10/761,338

Filed: JANUARY 22, 2004

19. (original) A photonic device according to claim 1 further comprising an optical signal conveying surface through which the output signal is coupled to another optical element either directly or through free space optics.

20. (original) A photonic device according to claim 1 wherein the wave guide is a plated wave guide formed in an opening in a resist prior to the resist being removed.

21. (currently amended) A photonic device according to claim 9 wherein optical pump source comprises an LED of a single wavelength or of multiple wavelengths that cover a particular absorption band of the type IV semiconductor nanocrystals.

22. (currently amended) A photonic device according to claim 9 further comprising a Holographic Optical Element for coupling an optical taper used to transmit the combined light signal away from the broadband optical source, the taper using Total Internal Reflection (TIR) to direct the broadband source to the wave guide.

23. (Cancelled)

24. (original) A photonic device according to claim 9 further comprising: at least one Holographic Optical Element (HOE) located after (downstream from) the optical pump source.

In re Patent Application of:

STEVEN HILL

Serial No. 10/761,338

Filed: JANUARY 22, 2004

25. (currently amended) A photonic device comprising:

an amplification medium comprising REDGIVN ~~REDGINV~~;

a plurality of light sources; and

a combiner adapted to combine light from the plurality of light sources to produce a broadband optical pump source, which pumps light into the amplification medium.

26. (original) A photonic device according to claim 25 wherein the plurality of light sources comprise a plurality of LEDs.

27. (currently amended) A photonic device according to claim 26 wherein the combiner comprises a ~~an~~ lens, wherein there is self-alignment of the operational wavelengths of the LED sources to the acceptance angle characteristics of the input lens.

28. (currently amended) A photonic device according to claim 27, wherein the lens is a Plano-convex aspherical cylindrical design that has a ~~small~~ F# and a ~~short~~ focal length to re-image the LED source and or sources to a planar output plane where the amplifying medium ~~median~~ is located; wherein the F# is a ratio of the lens focal length to the lens diameter.

29. (currently amended) A photonic device according to claim 25, wherein the combiner comprises a single reflector or multiple micro-reflectors to effectively couple ~~efficiently~~ the light signals into the broadband optical pump source.

In re Patent Application of:

STEVEN HILL

Serial No. 10/761,338

Filed: **JANUARY 22, 2004**

30. Canceled

31. Canceled

32. Canceled

33. Canceled

34. (previously presented) The photonic device according to claim 1, wherein the REDGIVN material includes one or more rare earth elements dispersed on the surface of semiconductor nanocrystals.

35. (currently amended) The photonic device according to claim 34, wherein the one or more rare earth elements are in a total concentration of from 0.5 to 15 atomic percent.